

# Andaman Cabriolet 39: Specification, Build Materials & Itemised Equipment / Fit-out List

- Length Overall 11.90 m
- Beam 6.05 m
- Headroom (Saloon) 1.90 m
- Headroom (Hulls) 2.00 m
- Under Wing Clearance 0.70 m
- Draft (boards up) 0.60 m
- Draft (boards down) 1.80 m
- Displacement 4,200 kg
- Lightships 3,800 kg

## Materials

- Where specification states 'foam' = DIAB © H80 Divinycell high density foam or equivalent – unless otherwise specified
  - Where specification states 'epoxy' = FGI © R180 Epoxy Resin or equivalent
  - Where specification states 'honeycomb' = Hexacore © PVC honeycomb laminate or equivalent
  - Where specification states 'plywood' = certified marine grade plywood
  - Hull & deck structures
    - Hull (upper and lower) – foam and epoxy using biaxial & woven fibreglass cloth
    - Exterior of hull & deck finish – gloss polyurethane; non-slip deck paint on upper surfaces
    - Deck – foam with glued and glassed alloy plates for fitting deck fittings. Stainless backing plates fitted where required.
  - Under wing – glassed foam
  - Main structural bulkhead and secondary bulkheads – foam, glassed fore and aft on hull & deck for optimum stiffness
  - Forward crossbeam – carbon fibre / epoxy laminate with stainless and aluminium fittings
  - Non-structural furniture – combination of honeycomb, H60 DIAB foam, with epoxy & woven cloth mat
  - Cockpit, transom and internal shower floors – non-slip deck paint
- NOTE: Layup of hulls to be effected using vacuum bagging techniques as directed by DIAB, manufacturer and supplier of foam materials for the vessel's hull and deck construction.

## Rig specifications (Allyacht Spars, Australia or equivalent)

- Mast height from base: 14.40 m
- Boom length: 4.93 m
- Furler Profurl C350 or equivalent
- Prodler alloy
- Chain plates – combination carbon fibre, stainless and woven fibre cloth / epoxy
- Running rigging

## Sails (UK Halsey, Rolly Tasker or equivalent)

- Main 45 sqm fully battened (with mainsail cover and lazy jacks)
- Jib 26 sqm
- Spinnaker asymmetrical 80 sqm

## Steering/rudder systems

- Fold back tillers x 2 with crosslink arm on roller ball cars and track
- Raymarine ST2000 TILLER Autopilot (or equivalent)

## Anchoring & mooring

- 6 x stainless steel or alloy mooring cleats 150mm
- 1 x Bow roller
- 1 x 16KG/35lb Manson (or equivalent) anchor with stainless swivel
- 50m x 8mm short link chain & 50m 12mm 3 strand rope
- Anchor bridle 3-strand rope 12mm
- Fenders inflatable x 4 (200 x 560mm)
- Maxwell RC10 8mm-5/16" 100TDC (or equivalent) anchor winch plus handheld pendant switch & breaker

## Dinghy

- Yachtsman 3.1m Hypalon RIB (or equivalent)
- 3HP outboard engine
- Dinghy davits with pulley system fitted to transom

## Deck hardware and fittings

- 2 x Harken 46-2STA self tailing primary winches (or equivalent)
- 2 x Harken 40-2STA self tailing secondary winches (or equivalent)
- 1 x Harken 35-2STA self tailing secondary winch (or equivalent)
- All other deck hardware Harken (or equivalent)
- Stanchions to sides and back – stainless steel with lifelines
- Swim ladder aft on transom – stainless steel
- Ferrari fabric mesh (or equivalent) trampolines

## Ports & hatches

- Cabin top complete with fixed side windows and 4 x forward opening Maxwell (or equivalent) hatches
- 4 x Maxwell (or equivalent) hatches, 1 over each single and 1 over each double berth
- 8 x Maxwell (or equivalent) side opening port lights (4 each hull)
- All other deck hatches fabricated in foam, epoxy/glass and fitted with hinges & latches

## Antifouling & painting

- 2 x coats of epoxy undercoat
- 2 x coats of antifouling – black
- Hull paint – white + colour of choice on lower hull (custom paintwork subject to price adjustment)

## Engines

- 2 x 9.9 HP (or equivalent), 4-stroke long shaft outboard engines
- Electric remote start
- Electric tilt
- Props 3-bladed
- Dual engine controls fitted to helm location
- Fuel – Petrol with CAV type pre-filters 1 filter per engine
- Engines are located under seats in cockpit compartments with access thru seats

## Electrical

- 2 x 180AH AGM house batteries in one bank
- 1 x 35AH dedicated engine start battery (All batteries fitted with retaining system)
- All relevant wiring leading back to switch panels with PTC fuses
- Inverter 1000W
- 2 x 240V outlets
- LED & energy saver lighting
- 2 x 135W Kyocera (or equivalent) solar panels with regulators

## Plumbing

- Pressure water system. Whale (or equivalent) pumps
- Pressure water to galley, bathroom and deck shower
- 2 x 12VDC electric big bowl TMC (or equivalent) toilet
- Black water treatment system by Saniloo™ (or equivalent) fitted to each toilet
- 4 x electric bilge pumps with automatic float switches and auto/manual switch panel + alarm

## Fuel & water

- Fuel capacity: 100 ltr (portable fuel containers with retaining system)
- Fresh water capacity: 600 ltr (2 x 300 ltr in-hull epoxy tanks)

## Navigation

- Raymarine ST60+ Wind System port & starboard (or equivalent)
- Raymarine ST60+ Tridata System (or equivalent)
- Raymarine RW A50 - 5" CHARTPLOTTER (or equivalent) with NMEA repeater
- 2 x Compass Suunto 95mm (or equivalent)

## Safety

- 2 x 2.3kg fire extinguishers
- 1 x Fire blanket
- 1 x gas detector in galley
- 1 x Spotlight 12V 100W
- 2 x Lifebuoys (or equivalent)

## Accommodation

- 2 x double cabins (1.95 m [6.4ft] depth)
- 2 x single cabins (bow)
- Zip Sunbrella (or equivalent) door to each cabin
- 1 x double convertible (saloon)

## Berths

- High density foam mattresses
- Cupboards
- Reading lights
- Hatch & side ports
- Fans 12VDC (double x 2 fans, single x 1 fan)

## Shower / toilets

- 2 x shower/toilets (aft hulls), including:
  - Epoxy / honeycomb moulded cupboard unit with shelves
  - Composite / epoxy moulded sink
  - 1 x wall mounted mirror
  - 1 x combination tap/shower unit with flexible hose
- Shower bilge pump (manual)
- Opening side port
- Lighting
- 1 x zip screen door (waterproof PVC one side) – locally manufactured, Sunbrella (or equivalent)

## Saloon/cockpit

- Retractable 'soft' roof section over saloon – locally manufactured, Sunbrella (or equivalent) over frame.
- Awning over cockpit – locally manufactured, Sunbrella (or equivalent) with alloy fixing posts
- Fitted settee in saloon to port
- Saloon table (removable to cockpit)
- Insert with cushion to convert saloon seating to double berth
- Aft zippered doors/screen – local manufacture, Sunbrella (or equivalent)
- 2 x iceboxes in aft beam
- 2 x concealed garbage bins in aft beam
- Ample cockpit seating with Sunbrella (or equivalent) covered cushions.

## Galley

- Galley to starboard of saloon with fitted cupboards and floor
- 2-burner stove, SMEV (or equivalent)
- Mini Grill, SMEV (or equivalent)
- Stainless steel sink, SMEV (or equivalent)
- Stainless steel tap
- Fridge / freezer, Waeco 12vDC
- 'Lazy Susan' carousel storage fitted under galley counter
- 1 x 4.5kg LP gas bottle servicing galley (located in forward wet locker)

## General

- Timber fiddles on various edges throughout the saloon and hulls
- Internal finish gloss
- Lighting – LED and/or energy saver lights
- Laminate teak effect flooring in hulls and saloon

*All weights and measurements herein are approximate. Specification subject to change. Final binding specifications will be attached to purchase agreement. Changes to specification after contract are subject to buyer's approval.*

## Composite Catamarans Co., Ltd.

90/5 Moo 2, Chaofa Road West, Vichit, Muang, Phuket 83000, Thailand

Tel. +66 (0)81 797 9754 Fax. +66 (0)76 264454

email. info@catamaransailingphuket.com www.catamaransailingphuket.com

